

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification 7 :</b> <b>A61K 7/32</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/35412</b> <b>(43) International Publication Date:</b> 22 June 2000 (22.06.00)
<b>(21) International Application Number:</b> PCT/US99/28459 <b>(22) International Filing Date:</b> 2 December 1999 (02.12.99)  <b>(30) Priority Data:</b> 09/224,106 17 December 1998 (17.12.98) US  <b>(71) Applicant:</b> HERCULES INCORPORATED [US/US]; 1313 North Market Street, Wilmington, DE 19894-0001 (US). <b>(72) Inventor:</b> MODI, Jashawant, J.; 57 Raphael Road, Bella Vista, Hockessin, DE 19707 (US). <b>(74) Agent:</b> EDWARDS, David; Hercules Incorporated, 1313 North Market Street, Wilmington, DE 19894-0001 (US).		<b>(81) Designated States:</b> AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
<b>(54) Title:</b> HYDROPHOBICALLY MODIFIED POLYSACCHARIDE IN ANHYDROUS ANTIPERSPIRANT PRODUCTS  <b>(57) Abstract</b>  A solid stick, underarm product composition is composed of a liquid vehicle, an antiperspirant salt, a dibenzylidene alditol gelling agent, and a co-gelling agent of a hydrophobically modified water soluble polysaccharide polymer which comprises a water soluble polysaccharide polymer backbone, a hydrophobic moiety of C <sub>8</sub> -C <sub>24</sub> alkyl, aryl alkyl, alkyl aryl groups and mixtures thereof, wherein the hydrophobic moiety is present in an amount up to the amount which renders said polysaccharide less than 1 % by weight soluble in water, and dibenzylidene alditol, antiperspirant active and a liquid vehicle. This underarm product can be either clear or hazy.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

5

10

## HYDROPHOBICALLY MODIFIED POLYSACCHARIDE IN ANHYDROUS ANTIPERSPIRANT PRODUCTS

This invention relates to the use of hydrophobically modified polysaccharides in underarm stick products such as antiperspirant/deodorant products.

15

### BACKGROUND OF THE INVENTION

Prior to the present invention, nonionic water-soluble cellulose ethers have been used in clear underarm stick products. Gel antiperspirant/ deodorant sticks typically include a liquid vehicle, an antiperspirant salt and/or deodorant agent, a gelling agent, and one or more emollients. Clear gel antiperspirant or deodorant sticks are more desirable than opaque sticks for cosmetic reasons. For clear sticks, the gelling agents of choice are dibenzylidene alditols, e.g., dibenzylidene sorbitol (DBS), also known as dibenzylidene monosorbitol acetal (DBMSA), because they are able to form strong free standing gels that are clear, are relatively stable, and have relatively good shelf life although they tend to degrade in certain environments. The degradation of the DBS is because of the presence of acidic antiperspirant salt in the stick. Commercially available DBS gel antiperspirant sticks generally contain more than 2% DBS in order to have sufficient hardness. However, such sticks do not have optimum clarity or stability.

Widely used commercially available nonionic water soluble cellulose ethers that are used in antiperspirant/deodorant sticks as co-gelling agents are, for example, methyl cellulose (MC), hydroxypropylmethylcellulose (HPMC), hydroxyethylcellulose (HEC), and hydroxypropylcellulose (HPC); HPC is preferred for clear antiperspirant/ deodorant sticks. The use of these prior art cellulose ethers in antiperspirant/ deodorant stick products sometimes have processing difficulties such as compatibility with other ingredients, solubility with certain other ingredients, clarity (when needed), and stability under alkaline conditions of the products.

40

- 5 International Publication Number WO 96/26709 and US Patents 5,705,171 and 5,725,846 disclose use of hydroxyalkylcellulose and specifically hydroxypropylcellulose in a clear anhydrous antiperspirant stick. US Patent 5,534,245 discloses use of a water-soluble cellulose polymer in a water containing roll-on or soft gel-like antiperspirant.
- 10 The stick form can be distinguished from a gel or a paste in that in a stick, the formulated product can maintain its shape for extended period of time outside the package except for the shrinkage due to solvent evaporation. US Patent 5,725,846, 5,705,171, 4,720,381, and 4,725,430 disclose use of hydroxypropylcellulose in a transparent anhydrous antiperspirant stick
- 15 composition. US Patent 4,383,988 discloses use of hydroxypropylcellulose acetate in water containing pourable antiperspirant gel composition. EP Patent Application 0260030 discloses the use of chemically modified cellulose, such as hydroxypropylcellulose, hydroxyethylcellulose, and methylcellulose in water containing clear deodorant sticks. However, none of the prior art discloses the
- 20 use of hydrophobically modified polysaccharides in a transparent anhydrous antiperspirant stick.

### SUMMARY OF THE INVENTION

- The present invention is directed to a solid stick antiperspirant/ deodorant
- 25 composition comprising (a) a liquid vehicle, (b) an antiperspirant salt, (c) dibenzylidene alditol gelling agent, and (d) a co-gelling agent of a hydrophobically modified water soluble polysaccharide polymer where the hydrophobic moiety is selected from the class consisting of C<sub>8</sub>-C<sub>24</sub> alkyl, aryl alkyl, alkyl aryl groups and mixtures thereof, wherein the hydrophobic moiety is
- 30 present in an amount up to the amount which renders said polysaccharide less than 1% by weight soluble in water.

### DETAILED DESCRIPTION OF THE INVENTION

- It has been found that hydrophobically modified water soluble non-ionic
- 35 polysaccharide polymer can be used as a co-gelling agent for certain solid stick, antiperspirant compositions that use dibenzylidene alditols as the gelling agent

- 5 to produce either comparable or superior products that are currently being marketed commercially.

Any water-soluble non-ionic polysaccharide can be used as the backbone to form the hydrophobically modified polysaccharide of this invention. Examples of water soluble non-ionic polysaccharides are cellulose ethers, guar and guar  
10 derivatives (e.g., hydroxyethyl guar or hydroxypropyl guar), and starch and starch derivatives (e.g., hydroxyethyl starch or hydroxypropyl starch).

A preferred backbone is cellulose ethers. Thus, e.g., hydroxyethylcellulose (HEC), hydroxypropylcellulose (HPC), methylcellulose (MC), hydroxypropylmethylcellulose (HPMC), ethylhydroxyethylcellulose  
15 (EHEC), methylhydroxyethylcellulose (MHEC) and their nonionic derivatives can all be as the backbone for the modification. The polysaccharide of this invention has to be water-soluble unmodified or has a sufficient degree of nonionic substitution to cause them to be water-soluble and a hydrophobic moiety of C<sub>8</sub>-C<sub>24</sub> alkyl, aryl alkyl, alkyl aryl groups and mixtures thereof. The hydrophobic  
20 moiety is present in an amount up to the amount that renders said polysaccharide less than 1% by weight soluble in water. When the hydrophobe is an alkyl, aryl alkyl, or alkyl aryl moiety, the number of carbon atoms has an upper limit of 24, preferably 22, more preferably 18, and most preferably 16. The lower limit of the carbon atoms of the hydrophobic moiety is 8 and preferably 12.

25 The preferred polysaccharide backbone is hydroxyethylcellulose (HEC) and hydroxypropylcellulose (HPC). The HEC that is modified to function in this invention is a commercially available material, that is marketed by the Aqualon Company, a division of Hercules Incorporated, Wilmington, Delaware U.S.A., under the trademarks Natrosol® *Plus* and Polysurf®.

30 The alkyl modifier group can be attached to the polysaccharide backbone via an ether, ester, or urethane linkage. Ether is the preferred linkage as the reagents most commonly used to effect etherification because it is readily obtainable; the reaction is similar to that commonly used for the initial etherification, and the reagents used in the reaction are usually more easily  
35 handled than the reagents used for modification via the other linkages. The resulting linkage is also usually more resistant to further reactions.

5       The hydrophobic moiety is generally contained in an amount of about 0.05 to about 10 wt. %, preferably about 0.1 to about 5 wt. based on the dry weight of the substituted polymer. Examples of modifying radicals are 2-ethylhexyl, octyl, cetyl, and octadecyl.

10

#### **Gelling agent**

Another essential ingredient of the present invention is the gelling agent dibenzylidene alditols such as dibenzylidene sorbitol (DBS) which is also known as dibenzylidene monosorbitol acetal (DBMSA), dibenzylidene xylitol, and dibenzylidene ribitol. The benzylidene group may be unsubstituted or  
15 substituted.

#### **Liquid Vehicle**

Another essential ingredient of the present invention is a liquid vehicle such as polyhydric alcohol having from 3 to 6 carbon atoms and 2 to 6 hydroxyl  
20 groups such as diethylene glycols, triethylene glycol, 1,2-propylene glycol, 1,3-propylene glycol, dipropyleneglycol, tripropylene glycol, 2-methyl-1,3-propendiol, butylene glycol, sorbitol, 2,4-dihydroxy-2-methylpentane, and the like, and mixtures thereof. The liquid vehicle may contain ethanol, isopropanol, or ethylene glycol.

25

#### **Antiperspirant Agent**

Another essential ingredient of the formulation is antiperspirant salts that have significant antiperspirant activity when applied to human skin. The salts may be inorganic or organic. It includes any of the conventional aluminum,  
30 zirconium, zinc and their combination known to be useful in antiperspirant compositions. These salts include aluminum halides, aluminum hydroxy halides, and mixtures or complexes thereof with zirconyl oxyhalides and zirconyl hydroxyhalides. It is preferred to use polyhydric alcohol solution of the antiperspirant salts. The solubilized form of some of the antiperspirant salts are  
35 commercially available such as Westchlor® A2Z 8106 from Westwood Chemical Corporation of Middletown, New York.

5

### Chelating Agent

Another ingredient that may be in the system is a chelating agent. Examples of chelating agents are salts of ethylenediamine tetraacetic acid (EDTA) such as tetra sodium ethylenediaminetetraacetate, ethanoldiglycine disodium salt (EDG), etc. The chelating agent may helps in improving color, clarity and as stabilizer for the gelling agent DBS.

10

### Emollient

Another ingredient that may be present in the system is an emollient such as fatty acid esters, e.g., isopropyl palmitate; diesters of adipic, phthalic, and sebacic acids; propylene glycol diesters of short chain fatty acids, nonvolatile silicone oils, volatile silicone oils; silicone elastomers, C<sub>12</sub>-C<sub>15</sub> alkyl benzoate; fatty alcohol such as stearyl alcohol; alkyl ether derivatives of polyethylene glycols, polypropylene glycols, and other emollients that are conventionally used in the personal care and cosmetic industry to enhance application properties of the sticks. An emollient can be used alone or in combination with other emollients in the present invention.

20

### Stabilizer

Another ingredient that may be present in the system is a stabilizer for dibenzylidene alditols such as sodium or potassium hydroxide; zinc compounds such as acetate, oxide, carbonate; di or triethanolamine; sodium benzoate or octanoate; urea; disodium succinate.

25

### Other Ingredients

Other ingredients that may be present in the system are fragrances, humectants, gel hardeners, fillers, colorants, preservatives, bactericides, UV absorbers, antioxidants, emulsifiers, activity enhancers, sunscreen, oils, and monohydric alcohols such as ethanol.

30

In accordance with the present invention, the underarm composition has by weight percent of about 70% to 95% liquid vehicle, about 0.5 % to 20 % antiperspirant salt, 0.3 % to 5.0 % dibenzylidene alditol, and 0.1 to 3.0 % hydrophobically modified water soluble polysaccharide.

35

5       The following examples are merely set forth for illustrative purposes, but it to be understood that other modifications of the present invention within the skill of artisans in the industry can be made without departing from the spirit and scope of the invention.

10

## EXAMPLES

In the following Examples, hydrophobically modified hydroxyalkyl-cellulose of HMHAC 1, HMHAC 2, Natrosol® Plus 430, and Polysurf® 67 products and were evaluated and compared with hydroxyalkylcellulose (HAC) such as Klucel® product in an antiperspirant (AP) formulation of the prior art.

### (A) Sample Preparation:

Examples 1 to 9 were prepared using two phase process (two step process). Example 10 was prepared using single phase (one step process). Briefly, in two phases, Gelling agents and the antiperspirant active ingredient were heated in separate vessels and then mixed together. In a single phase all ingredients of the formulation were mixed in a same container. More detail procedure for each example is attached.

### 25 (B) Samples Evaluations:

Table 1 provides comparative data for various HMHAC of this invention and for HAC (Klucel®). The samples were evaluated for:

30       Gel Strength  
Clarity  
Color  
Syneresis

Each formulation was stored at room temperature (about 25°C), 40°C, and at 5°C for at least one week and brought to about 25°C temperature prior to evaluating for the above characteristics.

**Gel Strength:** The gel strength was measured in grams using Voland-Stevens LFRA Texture Analyzer Unit with 0.5 inch (1.11mm) diameter probe. The probe



- 5 was lowered 2 mm into the gel at a speed of 2 mm/second. Three measurements were taken and the average of the three measurements was reported.

- 10 **Clarity:** Five subcategories were assigned to differentiate clarity differences between various samples. These were: Clear, Slightly Hazy, Hazy, Translucent, and Opaque.

- 15 **Clear:** Antiperspirant samples free from any material that dims, obscures, or darkens or prevents one from seeing an object located on the other side of it. For example, the 1/16" size print on a paper located behind the sample is easily and clearly readable.

- 20 **Slightly Hazy:** Antiperspirant samples through which 1/16" print is still readable but the print is not as sharp as with the "Clear" sample.

**Hazy:** Antiperspirant samples through which object located behind the sample can be still viewed and identified but are not as sharp as for the slightly hazy sample. The 1/16" prints are readable with some difficulty.

- 25 **Translucent:** Antiperspirant samples through which light is transmitted and an object can be identified but the image is fuzzy and not distinct. The 1/16" prints are not readable.

- 30 **Opaque:** The 1/16" print when located behind the sample cannot be seen or identified.

**Color:** Five subcategories were also assigned to differentiate clarity differences between various samples. These were water white, Light Yellow, Yellow, Dark Yellow, and Amber.

- 35 The colors and clarity were determined by a two person panel who are familiar with testing or rating samples; this panel rated the samples visually as compared to each other for clarity and color under ambient room light. In order

- 5 to insure consistency in the rating, all samples were rated at the same time under the same conditions.

**Syneresis:** It is the weeping out of liquid from the sample after standing for a period of time.

10

**Example A.**

**Formulation:**

<u>Phase 1:</u>	<u>Percent</u>
Propylene glycol	34.93
15 Millithix® 925	4.33
Subtotal	39.26
<u>Phase 2:</u>	
20 Propylene glycol	20.60
Tetrasodium EDTA	0.22
Westchlor® A2Z8106	39.65
Abil® B8851	0.27
Subtotal	60.74
25 Total	100.00

**Procedure:**

**Phase 1.**

- 30 Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol in the beaker was heated to about 125-130°C while stirring at the minimum speed of about 50 rpm with a Caframo Model RZR1 electric
- 35 mixer equipped with a Jiffy Model HS150 2.62 inch diameter mixer. The mixer speed was increased to about 150-200 rpm and the Millithix material was added at a temperature of about 120°C and mixed for 60 minutes until dissolved.

5 Phase 2.

Approximately one-third of the total propylene glycol was charged to a 600 ml beaker and immersed in a circulating water bath. The propylene glycol in the beaker was heated to about 80-85°C while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propeller blade. The EDTA was added at a temperature of about 80-85°C and mixed well to disperse. The mixer speed was increased to about 150-200 rpm and the Westchlor material was added at 82°C while mixing and mixed for five minutes. The Abil material was then added at 80°C while mixing and mixed for five minutes.

15

Combined Phases:

Phase 2, at 82°C, was added to Phase 1 at 132°C while mixing and mixed for five minutes at reduced speed to avoid air entrainment. The combined solution was re-heated to 125°C, then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

20

Source and Description of Products UsedExample A.

25	Propylene glycol		EM Industries, Inc. Gibbstown, NJ
	Millithix 925	Dibenzylidene sorbitol	Milliken Chemicals Spartanburg, SC
30	Tetrasodium EDTA		J.T.Baker co. Phillipsberg, NJ
	Westchlor A2Z 8106	Al/Zr Pentachlorohydrex-gly	Westwood Chemical Corp. Middletown, NY
35	Abil B8851	Dimethicone copolymer	Goldschmidt Chemical Corp. Hopewell, VA

5

**Example B****Formulation:**

<u>Phase 1:</u>	<u>Percent</u>
Propylene glycol	36.10
HMHAC1*	1.12
Subtotal	37.22

10

**Phase 2:**

Propylene glycol	21.30
Tetrasodium EDTA	0.22
Westchlor A2Z8106	40.98
Abil B8851	0.28
Subtotal	62.78

15

Total 100.00

20

**Procedure:****Phase 1.**

Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol in the beaker was heated to about 120-125°C while stirring at the minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150 2,62 inch diameter mixer. The HMHAC1 was added at about 75-80°C while mixing and the mixture was continued heating to about 125-130°C.

25

30

**Phase 2.**

Approximately one-third of the total propylene glycol was charged to a 600 ml beaker and immersed in a circulating water bath. The propylene glycol in the beaker was heated to about 80-85°C while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The EDTA was added at about 60-65°C and mixed well to disperse. The mixer speed was increased to about 150-200 rpm and the Westchlor material was added at about 82°C while mixing and mixed for five

35

- 5 minutes. The Abil material was then added at about 75-80°C while mixing and mixed for five minutes.

Combined Phases:

- Phase 2, at about 81°C, was added to Phase 1 at about 126°C while mixing and mixed for five minutes at reduced speed to avoid air entrainment. The combined solution was re-heated to about 120°C, then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

- 15 \*HMHAC1 is hydrophobically modified hydroxyethylcellulose that contains a long chain (C<sub>16</sub>) alkyl group and has Brookfield viscosity of 25 cps at about 1.0% at 25°C.

Example 1

20 Formulation:

<u>Phase 1:</u>	<u>Percent</u>
Propylene glycol	34.55
HMHAC1	1.07
Millithix 925	4.29
25 Subtotal	39.91

Phase 2:

Propylene glycol	20.38
Tetrasodium EDTA	0.21
30 Westchlor A2Z8106	39.22
Abil B8851	0.27
Subtotal	60.09

Total 100.00

35

Procedure:

Phase 1.

- Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol was heated to about 120-125°C while stirring at the

40

- 5 minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150 2.62 inch diameter mixer. The HMHAC1 was added at about 75-80°C while mixing and the mixture was continued to be heated to about 105-110°C. The mixer speed was increased to about 150-200 rpm and the Millithix material was added at about 120°C and mixed for 90 minutes until  
10 dissolved.

### Phase 2.

- Approximately one-third of the total propylene glycol was charged to a 600 ml beaker and immersed in a circulating water bath. The propylene glycol in  
15 the beaker was heated to about 80-85°C while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The EDTA was added at about 80-85°C and mixed well to disperse. The mixer speed was increased to 150-200 rpm and the Westchlor material was added while mixing and mixed for five minutes. The Abil  
20 product then was added at about 75-80°C while mixing and mixed for five minutes.

### Combined Phases:

- When the Millithix material was all dissolved, Phase 2, at about 81°C, was  
25 added to Phase 1 at about 130°C while mixing and mixed for five minutes at reduced speed to avoid air entrainment. The combined solution was re-heated to about 120°C, then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

30

### Example C

#### Formulation:

<u>Phase 1:</u>	<u>Percent</u>
Propylene glycol	36.18
Klucel® MFF*	0.34
35 Millithix 925	0.56
Subtotal	37.08

5 Phase 2:

Propylene glycol	21.34
Tetrasodium EDTA	0.22
Westchlor A2Z8106	41.07
Abil B8851	0.28

10

Subtotal	62.92
Total	100.00

Procedure:15 Phase 1.

Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol in the beaker was heated to about 85-90°C while stirring at ~450-500 rpm with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The Klucel MFF polymer was added at about 85-90°C while mixing and the mixture was continued heating to about 105-110°C. The Millithix material was then added and mixed for about 40 minutes until dissolved.

25

Phase 2.

Approximately one-third of the total propylene glycol was charged to a 600 ml beaker and immersed in a circulating water bath. The propylene glycol in the beaker was heated to about 65-70°C while stirring at ~450-500 rpm with a Caframo Model RZR1 electric mixer equipped with a single 1½" diameter propellor blade. The EDTA was added at about 65-70°C and mixed well to disperse. The Westchlor material was added while mixing and mixed for five minutes. The Abil material was then added while mixing and mixed for five minutes.

35

\*Klucel MFF is the trademark that covers hydroxypropylcellulose that is nonionic and has a Brookfield viscosity of 4,000 to 6,500 at 2.0% at 25°C.

5

**Combined Phases:**

When the Millithix material was all dissolved, Phase 1 was cooled to about 95-100°C. Phase 2 was then added to Phase 1 while mixing and mixed for five minutes at minimum speed to avoid air entrainment. The combined solution at about 80-85°C was then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

**Example 2****Formulation:**

<u>Phase 1:</u>	<u>Percent</u>
15 Propylene glycol	36.18
Natrosol® Plus 430*	0.34
Millithix 925	0.56
Subtotal	37.08
20	
<u>Phase 2:</u>	
Propylene glycol	21.34
Tetrasodium EDTA	0.22
Westchlor A2Z8106	41.07
25 Abil B8851	0.28
Subtotal	62.92
Total	100.00

**Procedure:****Phase 1.**

Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol was heated to about 70-75°C while stirring at a minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150 2.62 inch diameter mixer. The Natrosol® Plus 430 product

40

\*Natrosol ®Plus 430 is the trademark that covers nonionic hydrophobically modified hydroxyethylcellulose. It has long chain (C<sub>18</sub>) alkyl group and an aqueous , Brookfield viscosity at 1.0% of between 5000-9000 cps at spindle 3, 6rpm.



- 5 was added at about 70-75°C while mixing and the mixture was continued heating to about 105-110°C. The mixer speed was increased to about 150-200 rpm and the Millithix material was added at about 105-110°C and mixed for 40 minutes until dissolved.

10 Phase 2.

- Approximately one-third of the total propylene glycol was charged to a 600 ml beaker and immersed in a circulating water bath. The propylene glycol in the beaker was heated while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The mixer speed was increased to about 150-200 rpm and the EDTA was added at about 60-65°C and mixed well to disperse. The Westchlor material was added while mixing and mixed for five minutes. The Abil material then was added while mixing and mixed for five minutes.

20 Combined Phases:

- When the Millithix material was all dissolved, Phase 1 was cooled to about 105-110°C. Phase 2 was then added to Phase 1 while mixing and mixed for five minutes at reduced speed to avoid air entrainment. The combined solution at about 95-100°C was then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

5

**Example 3****Formulation:**

<u>Phase 1:</u>	<u>Percent</u>
Propylene glycol	36.18
Polysurf 67*	0.34
10 Millithix 925	0.56
Subtotal	37.08
 <u>Phase 2:</u>	
15 Propylene glycol	21.34
Tetrasodium EDTA	0.22
Westchlor A2Z8106	41.07
Abil B8851	0.28
20 Subtotal	62.92
Total	100.00

**Procedure:****Phase 1.**

25        Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker paper was kept covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol was heated while stirring at the minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy  
30 Model HS150 2.62 inch diameter mixer. The Polysurf 67 material was added at 60-65°C while mixing and the mixture was continued to heat to about 110-115°C. The mixer speed was increased to about 150-200 rpm and the Millithix material was added and mixed for about 20 minutes until dissolved.

35

40        \*Polysurf 67 is a trademark that covers nonionic hydrophobically modified hydroxyethylcellulose. It has long chain (C<sub>16</sub>) alkyl group and an aqueous Brookfield viscosity at 1.0% of between 6000-13000cps, at spindle 3, 6rpm.

5 Phase 2.

Approximately one-third of the total propylene glycol was charged to about 600 ml beaker and immersed in a circulating water bath. The propylene glycol was heated in a beaker while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter  
10 propellor blade. The EDTA was added at about 65-70°C and mixed well to disperse. The mixer speed was increased to 150-200 rpm and the Westchlor material was added while mixing and mixed for five minutes. The Abil material then was added while mixing and mixed for five minutes.

15 Combined Phases:

When the Millithix material was all dissolved, Phase 1 was cooled to about 105-110°C. Phase 2 was then added to Phase 1 while mixing and mixed for five minutes at reduced speed to avoid air entrainment. The combined  
20 solution at about 85-90°C was then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

**Example D****Formulation:**

	<b><u>Phase 1:</u></b>	<b><u>Percent</u></b>
25	Propylene glycol	35.90
	Klucel MFF	0.56
	Millithix 925	1.11
	Subtotal	37.57
30		
	<b><u>Phase 2:</u></b>	
	Propylene glycol	21.18
	Westchlor A2Z8106	0.22
	Tetrasodium EDTA	40.75
35	Abil B8851	0.28
	Subtotal	62.43
	Total	100.00

5 **Procedure:****Phase 1.**

Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles.

10 The propylene glycol was heated to about 125-130°C while stirring at the minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150 2.62 inch diameter mixer. The Klucel MFF material was added at about 60-65°C, and the mixture was continued heating to about 120-130°C. The mixer speed was increased to 150-200 rpm and the Millithix

15 material was added at about 120°C and mixed for about 40 minutes to dissolve.

**Phase 2.**

Approximately one-third of the total propylene glycol was charged to about 600 ml beaker and immersed in a circulating water bath. The propylene

20 glycol was heated in a beaker to about 80-85°C while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The EDTA was added at about 75-80°C and mixed well to disperse. The mixer speed was increased to 150-200 rpm and the Westchlor was added at about 80-85°C while mixing and mixed. The Abil was

25 then added at about 70-75°C while mixing and mixed for about 20 minutes.

**Combined Phases:**

Phase 2, at about 82°C, was added to Phase 1 at about 131°C while mixing and mixed for about 10 minutes at reduced speed to avoid air

30 entrainment. The combined solution was re-heated to about 120-125°C while mixing, then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

5

**Example 4****Formulation:**

<u>Phase 1:</u>		<u>Percent</u>
	Propylene glycol	35.90
	HMHAC2*	0.56
10	Millithix 925	1.11
	Subtotal	37.57
 <u>Phase 2:</u>		
15	Propylene glycol	21.18
	Tetrasodium EDTA	0.22
	Westchlor A2Z8106	40.75
	Abil B8851	0.28
	Subtotal	62.43
20	Total	100.00

**Procedure:****Phase 1.**

25 Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol was heated to about 125-130°C while stirring at the minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150 2.62 inch diameter mixer. The HMHAC2 was added at  
30 about 75-80°C, and the mixture was continued heating to about 120-130°C. The mixer speed was increased to about 150-200 rpm and the Millithix material was added at about 120°C and mixed for 30 minutes to dissolve.

**Phase 2.**

35 Approximately one-third of the total propylene glycol was charged to about 600 ml beaker and immersed in a circulating water bath. The propylene glycol was

40 \*HMHAC2 is a nonionic (C8) alkylated hydroxypropylcellulose polymer.

- 5 heated in a beaker to about 80-85°C while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The EDTA was added at about 75-80°C and mixed well to disperse. The mixer speed was increased to about 150-200 rpm and the Westchlor material was added at about 80-85°C while mixing and mixed. The  
10 Abil material was then added at about 80-85°C while mixing and mixed for ten minutes.

Combined Phases:

- Phase 2, at about 82°C, was added to Phase 1 at about 131°C while  
15 mixing and mixed for about 10 minutes at reduced speed to avoid air entrainment. The combined solution was re-heated to about 120-125°C while mixing, then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

20

Example 5

Formulation:

<u>Phase 1:</u>		<u>Percent</u>
	Propylene glycol	35.90
	Natrosol® Plus 430	0.56
25	Millithix 925	1.11
	<b>Subtotal</b>	<b>37.57</b>
 <u>Phase 2:</u>		
30	Propylene glycol	21.18
	Tetrasodium EDTA	0.22
	Westchlor A2Z8106	40.75
	Abil B8851	0.28
	<b>Subtotal</b>	<b>62.43</b>
35	<b>Total</b>	<b>100.00</b>

Procedure:

Phase 1.

- Approximately two-thirds of the total propylene glycol was charged to a  
40 one-liter beaker and immersed in a circulating oil bath. The beaker was kept

- 5 covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol was heated to about 125-130°C while stirring at the minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150 2.62 inch diameter mixer. The Natrosol® Plus 430 material was added at about 75-80°C, and the mixture was continued heating to  
10 about 120-130°C. The mixer speed was increased to 150-200 rpm and the Millithix material was added at about 120°C and mixed for about 40 minutes to dissolve.

#### Phase 2.

- 15 Approximately one-third of the total propylene glycol was charged to about 600 ml beaker and immersed in a circulating water bath. The propylene glycol was heated to about 80-85°C while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The EDTA was added at 80-85°C and mixed well to  
20 disperse. The mixer speed was increased to 150-200 rpm and the Westchlor material was added at about 80-85°C while mixing and mixed. The Abil material was then added at about 80-85°C while mixing and mixed for five minutes.

#### Combined Phases:

- 25 Phase 2, at about 80-85°C, was added to Phase 1 at about 130°C while mixing and mixed for about 15 minutes at reduced speed to avoid air entrainment. The combined solution was re-heated to about 120-125°C while mixing, then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

5

**Example 6****Formulation:**

<u>Phase 1:</u>	<u>Percent</u>
Propylene glycol	35.50
Natrosol® Plus 430	0.55
10 Millithix 925	1.10
Crodacol C-95	1.10
Subtotal	38.26
15 <u>Phase 2:</u>	
Propylene glycol	20.94
Tetrasodium EDTA	0.22
Westchlor A2Z8106	40.30
20 Abil B8851	0.28
Subtotal	61.74
Total	100.00

**Procedure:**25 **Phase 1.**

Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol was heated to about 125-130°C while stirring at the  
30 minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150 2.62 inch diameter mixer. The Natrosol® Plus 430 material was added at about 105-110°C, and the mixture was continued heating to about 120-130°C. The mixer speed was increased to 150-200 rpm and the  
35 Millithix material was added at about 120°C and mixed for about 40 minutes to dissolve. The Crodacol C-95 was then added at about 132°C and mixed for about 15 minutes.

**Phase 2.**

40 Approximately one-third of the total propylene glycol was charged to a 600 ml beaker and immersed in a circulating water bath. The propylene glycol



- 5 was heated in beaker to about 80-85°C while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The EDTA was added at 75-80°C and mixed well to disperse. The mixer speed was increased to 150-200 rpm and the Westchlor material was added at about 80-85°C while mixing and mixed until. The Abil  
10 material was then added at about 80-85°C while mixing and mixed for about five minutes.

Combined Phases:

- Phase 2, at about 82°C, was added to Phase 1 at about 131°C while  
15 mixing and mixed for about 15 minutes at reduced speed to avoid air entrainment. The combined solution was re-heated to about 120-125°C while mixing, then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

Example 7

20 Formulation:

Phase 1:

Percent

Propylene glycol	35.31
Natrosol® Plus 430	0.55
Millithix 925	1.10
25 Crodacol C-95	1.10

**Subtotal**

**38.05**

Phase 2:

30 Propylene glycol	20.83
Tetrasodium EDTA	0.22
Westchlor A2Z8106	40.08
Abil B8851	0.27

35 **Subtotal**

**61.41**

Phase 3:

Fragrance SL91-2007	0.55
---------------------	------

**Total**

**100.00**

40

5 **Procedure:****Phase 1.**

Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles.

- 10 The propylene glycol was heated to about 125-130°C while stirring at the minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150 2.62 inch diameter mixer. The Natrosol® *Plus* 430 material was added at about 85-90°C, and the mixture was continued heating to about 120-130°C. The mixer speed was increased to about 150-200 rpm and the
- 15 Millithix material was added at about 120°C and mixed for about 25 minutes to dissolve. The Crodacol C-95 material was then added at about 130°C and mixed for about 15 minutes.

**Phase 2.**

- 20 Approximately one-third of the total propylene glycol was charged to about 600 ml beaker and immersed in a circulating water bath. The propylene glycol was heated in a beaker to about 80-85°C while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The EDTA was added at about 55-60°C and
- 25 mixed well to disperse. The mixer speed was increased to about 150-200 rpm and the Westchlor material was added at about 80-85°C while mixing and mixed. The Abil material was then added at about 80-85°C while mixing and mixed for about ten minutes.

30 **Combined Phases:**

- Phase 2, at about 82°C, was added to Phase 1 at about 131°C while mixing and mixed for about 10 minutes at reduced speed to avoid air entrainment. The fragrance was injected into the combined solution with a syringe through the saran cover to minimize loss. The batch at about 120-125°C
- 35 was then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

5

**Source and Description of Products Used****Example 7**

10	Crodacol C-95	Cetyl alcohol	Croda, Inc. Parsippany, NJ
	SL91-2007	Fragrance, Masculine IV	PFW, Inc. Middletown, NY

15

**Example 8****Formulation:**

	<b><u>Phase 1:</u></b>	<b><u>Percent</u></b>
	Propylene glycol	35.54
	HMHAC1	0.99
20	Millithix 925	1.65
	Subtotal	38.19
	<b><u>Phase 2:</u></b>	
25	Propylene glycol	20.97
	Tetrasodium EDTA	0.22
	Westchlor A2Z8106	40.35
	Abil B8851	0.28
30	Subtotal	61.81
	Total	100.00

**Procedure:****Phase 1.**

35        Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol was heated while stirring at the minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150  
40        2.62 inch diameter mixer. The HMHAC1 material was added at about 75-80°C while mixing and the mixture was continued to heat to about 105-110°C. The

- 5 mixer speed was increased to about 150-200 rpm and the Millithix material was added and mixed for about 15 minutes until dissolved.

### Phase 2.

- Approximately one-third of the total propylene glycol was charged to a  
10 600 ml beaker and immersed in a circulating water bath. The propylene glycol was heated in a beaker to about 80-85° while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The EDTA was added at about 45-50°C and mixed well to disperse. The mixer speed was increased to about 150-200 rpm and the  
15 Westchlor material was added at about 55-60°C while mixing and mixed for five minutes until clear and homogeneous. The Abil material then was added at about 75-80°C while mixing and mixed for five minutes.

### Combined Phases:

- 20 When the Millithix material was all dissolved, Phase 2, at about 77°C, was added to Phase 1 at about 125°C while mixing and mixed for five minutes at reduced speed to avoid air entrainment. The combined solution was re-heated to about 120°C, then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

25

### Example 9

#### Formulation:

##### Phase 1:

	<u>Percent</u>
Propylene glycol	35.50
30 Polysurf 67	1.10
Millithix 925	1.65
Subtotal	38.26

##### Phase 2:

35 Propylene glycol	20.94
Tetrasodium EDTA	0.22
Westchlor A2Z8106	40.30
Abil B8851	0.28
Subtotal	61.74
40 Total	100.00

5    **Procedure:**      **Phase 1.**

Approximately two-thirds of the total propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles.

10   The propylene glycol was heated to about 125-130°C while stirring at the minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150 2.62 inch diameter mixer. The Polysurf 67 material was added at about 90-95°C while mixing for about 15 minutes, and the mixture was continued heating to about 120-130°C. The mixer speed was increased to

15   about 150-200 rpm and the Millithix material was added at about 120°C and mixed for about 40 minutes to dissolve.

**Phase 2.**

Approximately one-third of the total propylene glycol was charged to

20   about 600 ml beaker and immersed in a circulating water bath. The propylene glycol was heated in a beaker to about 80-85°C while stirring at minimum speed (~50 rpm) with a Caframo Model RZR1 electric mixer equipped with a single two-inch diameter propellor blade. The EDTA was added at about 70-75°C and mixed well to disperse. The mixer speed was increased to about 150-200 rpm

25   and the Westchlor material was added while mixing and mixed. The Abil material was then added at about 80-85°C while mixing and mixed for about five minutes.

**Combined Phases:**

30   Phase 2, at about 80-85°C, was added to Phase 1 at about 130°C while mixing and mixed for about five minutes at reduced speed to avoid air entrainment. The combined solution was re-heated to about 125-130°C while mixing an additional about 20 minutes to dissolve a few remaining particles, then poured into four four-ounce jars and four 17-ml vials for testing and allowed to

35   cool to room temperature.

5

**Example 10****Formulation:**

	<u>Percent</u>
Propylene glycol	56.45
10 Polysurf 67	1.10
Millithix 925	1.65
Tetrasodium EDTA	0.22
Westchlor A2Z8106	40.30
Abil B8851	0.28
15 <b>Subtotal</b>	<b>100.00</b>

**Procedure:****Phase 1.**

20 The propylene glycol was charged to a one-liter beaker and immersed in a circulating oil bath. The beaker was kept covered with saran wrap throughout the preparation to minimize loss of volatiles. The propylene glycol was heated to about 120-130°C while stirring at the minimum speed of ~50 rpm with a Caframo Model RZR1 electric mixer equipped with a Jiffy Model HS150 2.62 inch diameter mixer. The Polysurf 67 material was added at about 60-65°C, and the  
25 mixture was continued heating to about 120-130°C. The mixer speed was increased to about 150-200 rpm and the Millithix material was added at about 107°C and mixed for about 60 minutes at about 120-130°C to dissolve. The EDTA, Westchlor material were added in order at about 130°C and mixed five minutes after each addition. The Abil material was added at about 104°C and  
30 mixed at about 15 minutes. The combined solution was re-heated to about 120-125°C while mixing, then poured into four four-ounce jars and four 17-ml vials for testing and allowed to cool to room temperature.

5 What is claimed:

1. A solid stick underarm product composition comprising (a) a liquid vehicle, (b) an antiperspirant salt, (c) dibenzylidene alditol gelling agent, and (d) a co-gelling agent of a hydrophobically modified water soluble polysaccharide polymer where the hydrophobic moiety is selected from the class consisting of  
10 C<sub>8</sub>-C<sub>24</sub> alkyl, aryl alkyl, alkyl aryl groups and mixtures thereof, wherein the hydrophobic moiety is present in an amount up to the amount which renders said polysaccharide less than 1% by weight soluble in water.
- 15 2. The solid stick underarm product composition of claim 1, wherein the liquid vehicle is a polyhydric alcohol having from 3 to 6 carbon atoms and 2 to 6 hydroxyl group.
- 20 3. The solid stick underarm product composition of claim 2, wherein the liquid vehicle is selected from the group consisting of diethylene glycols, triethylene glycols, 1,2-propylene glycol, 1,3-propylene glycol, dipropyleneglycol, tripropylene glycol, 2-methyl-1,3-propendiol, butylene glycol, sorbitol, 2,4-dihydroxy-2-methylpentane, and the like, and mixtures thereof.
- 25 4. The solid stick underarm product composition of claim 1 wherein the liquid vehicle contains a member selected from the group consisting of ethanol, isopropanol, and ethylene glycol.
- 30 5. The solid stick underarm product composition of claim 2, wherein the liquid vehicle is propylene glycol.
6. The solid stick underarm product composition of claim 1, wherein the antiperspirant salt is selected from the group consisting of a salt of aluminum, zirconium, zinc and mixtures thereof.

35

5           7.     The solid stick underarm product composition of claim 6, wherein  
the antiperspirant salt is selected from the group consisting of aluminum halides,  
aluminum hydroxy halides, and mixtures.

8.     The solid stick underarm product composition of claim 7, wherein  
10 the antiperspirant salt is a complex thereof with zirconyl oxyhalides or zirconyl  
hydroxyhalides.

9.     The solid stick underarm product composition of claim 8, wherein  
the antiperspirant salt is aluminum zirconium pentacholorhydratex-gly dissolved  
15 in propylene glycol.

10.    The solid stick underarm product composition of claim 1, wherein  
the dibenzylidene alditol gelling agent is selected from the group consisting of  
dibenzylidene sorbitol (DBS), dibenzylidene monosorbitol acetal (DBMSA),  
20 dibenzylidene xylitol, and dibenzylidene ribitol.

11.    The solid stick underarm product composition of claim 10, wherein  
the dibenzylidene alditol gelling agent is dibenzylidene sorbitol.

25       12.    The solid stick underarm product composition of claim 1, wherein  
the underarm composition has by weight percent of from about 70% to about  
95% liquid vehicle, about 0.5% to about 20% antiperspirant salt, about 0.3% to  
about 5.0% dibenzylidene alditol, and about 0.1 to about 3.0% hydrophobically  
modified water soluble polysaccharide.

30       13.    The solid stick underarm product composition of claim 1, wherein  
the hydrophobically modified water soluble polysaccharide has a backbone that  
is selected from the group consisting of cellulose ethers, guar and guar  
derivatives, and starch and starch derivatives.

35       14.    The solid stick underarm product composition of claim 13, wherein  
the polysaccharide backbone is a cellulose ether.



5

15. The solid stick underarm product composition of claim 14, wherein polysaccharide backbone is selected from the group consisting of hydroxyethylcellulose (HEC), hydroxypropylcellulose (HPC), methylcellulose (MC), hydroxypropylmethylcellulose (HPMC), ethylhydroxyethylcellulose (EHEC), and methylhydroxyethylcellulose (MHEC, and mixtures thereof.

10

16. The solid stick underarm product composition of claim 15, wherein the polysaccharide backbone is HEC.

15

17. The solid stick underarm product composition of claim 15, wherein the polysaccharide backbone is HPC.

20

18. The solid stick underarm product composition of claim 13, wherein the guar derivative is hydroxyethyl guar or hydroxypropyl guar.

19. The solid stick underarm product composition of claim 13, wherein the starch derivative is hydroxyethyl starch or hydroxypropyl starch.

25

20. The solid stick underarm product composition of claim 13, wherein the hydrophobic moiety is attached to the backbone via ether, ester, or urethane linkage.

30

21. The solid stick underarm product composition of claim 20, wherein the linkage is ether.

22. The solid stick underarm product composition of claim 1, wherein the hydrophobic moiety has an upper limit of 22 carbons.

23. The solid stick underarm product composition of claim 1, wherein the hydrophobic moiety has an upper limit of 18 carbons.

35

5           24.    The solid stick underarm product composition of claim 1, wherein the hydrophobic moiety has a lower limit of 12 carbons.

          25.    The solid stick underarm product composition of claim 1, wherein the hydrophobic moiety is cetyl.

10

          26.    The solid stick underarm product composition of claim 1, wherein the hydrophobic moiety is octyl.

          27.    The solid stick underarm product composition of claim 1, wherein  
15 the composition further comprises at least one member selected from the group consisting of chelating agent, emollient, stabilizer, fragrance, color, filler, humectant, UV absorbers, sunscreen, antioxidant, and bactericide.

          28.    The solid stick underarm product composition of claim 27, wherein  
20 the emollient is at least one member selected from the group consisting of fatty acid esters, diesters of adipic, phthalic, and sebacic acids, propylene glycol diesters of short chain fatty acids, nonvolatile silicone oils, volatile silicone oils, silicone elastomers, C<sub>12</sub> - C<sub>15</sub> alkyl benzoate, fatty alcohols, alkyl ether derivatives of polyethylene glycols, polypropylene glycols, and mixtures thereof.

25           29.    The solid stick underarm product composition of claim 27, wherein the chelating agent is selected from salts of ethylenediamine tetraacetic acid (EDTA).

          30.    The solid stick underarm product composition of claim 27, wherein  
30 the stabilizer is selected from the group consisting of sodium or potassium hydroxide, zinc acetate, zinc oxide, zinc carbonate, di or tri-ethanolamine, sodium benzoate, sodium octanoate, urea, and disodium succinate.

          31.    The solid stick underarm product composition of claim 1, wherein  
35 the composition is a clear or hazy solid stick product.

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/28459

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61K7/32

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 878 189 A (HERCULES INCORPORATED) 18 November 1998 (1998-11-18) claims 1-41; example 14	1-31
A	WO 96 26709 A (THE GILLETTE COMPANY) 6 September 1996 (1996-09-06) the whole document & US 5 705 171 A cited in the application	1-31
A	EP 0 260 030 A (UNILEVER) 16 March 1988 (1988-03-16) cited in the application the whole document	1-31

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

24 May 2000

Date of mailing of the international search report

31/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Fischer, J.P.

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/28459

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 878189	A	18-11-1998	AU 6486598 A	12-11-1998
			BR 9801619 A	01-06-1999
			CA 2237367 A	12-11-1998
			CN 1203070 A	30-12-1998
			JP 11005801 A	12-01-1999
			SG 68671 A	16-11-1999
			ZA 9804001 A	12-11-1998
WO 9626709	A	06-09-1996	US 5725846 A	10-03-1998
			AU 5301096 A	18-09-1996
			BR 9607142 A	25-11-1997
			CA 2214577 A	06-09-1996
			CN 1181005 A	06-05-1998
			EP 0812183 A	17-12-1997
			JP 11501037 T	26-01-1999
			NZ 305082 A	28-10-1999
			US 5705171 A	06-01-1998
			ZA 9601649 A	16-07-1996
EP 260030	A	16-03-1988	AT 81966 T	15-11-1992
			AU 590959 B	23-11-1989
			AU 7739487 A	03-03-1988
			BR 8704413 A	19-04-1988
			CA 1296645 A	03-03-1992
			DE 3782479 A	10-12-1992
			DE 3782479 T	29-04-1993
			JP 1797943 C	12-11-1993
			JP 5007364 B	28-01-1993
			JP 63068518 A	28-03-1988
			ZA 8706402 A	26-04-1989